

Fluke i2500-10 iFlex® 柔性电流探头柔性电流探头



主要特性

- Expands the measurement range to 2500 A AC while providing increased display flexibility, Ability to measure awkward sized conductors and improved wire access
- CAT IV 600 V, CAT III 1000 V
- 7.5 mm coil diameter allows measurement in tight spaces
- Ergonomic design allows easy operation with one hand
- 1.8 m (6 ft) Cable
- Three-year warranty

How to Open the i2500-18 and i2500-10 iFlex® Flexible Current Probes:

Twist to Unlock

Pull to Open

Safety Conformance

IEC 61010-2-032 CAT III 1000 V / CAT IV 600 V

产品概述: Fluke i2500-10 iFlex® 柔性电流探头柔性电流探头

Be Ready for Anything

The Fluke iFlex® flexible current probes expand the measurement range of the select Fluke meters to 2500 A AC while providing the ultimate measurement flexibility. The iFlex® probes connect directly to the meter, displaying current measurements without error prone scaling factors. The 1.8 m (6 ft) cord allows separation between the measurement location and the clamp meter making it easier to view the display. The large loop size and thin cross section allow measurement of awkward sized conductors and improved wire access in crowded spaces. Available in 25 cm (10 in) and 45 cm (18 in) sizes.

产品规格: Fluke i2500-10 iFlex® 柔性电流探头柔性电流探头

Specifications			
	Range	Resolution	Accuracy
AC Current ¹	2500 A	0.1 A	3% ±5 digits ²
Frequency ¹	500 Hz	0.1 Hz	0.5% ±5 digits
External magnetic field rejection (with cable > 10 cm from the coupling)	40 dB		
Inrush ¹	·		
Safety rating	CAT III 1000 V, CAT IV 600 V		
1. When used with compatible Fluke meter. Accuracy stated includes probe and meter accuracy. 2. For position accuracy at non-optimum positions, see Position sensitivity specifications table “A”			
Position sensitivity specifications			
Distance from Optimum	i2500-10	Additional iFlex® Error	
A	0.5 in (12.7 mm)	±0.5%	
B	0.8 in (20.3 mm)	±1.0%	
C	1.4 in (35.6 mm)	±2.0%	
Measurement uncertainty assumes centralized primary conductor at optimum position, no external electrical or magnetic field, and within operating temperature.			

型号



Fluke i2500 10

i2500-10 iFlex® 柔性电流探头

Fluke. 让您的工作畅通无阻。

福禄克测试仪器（上海）有限公司 电话：400-810-3435 ©2026 福禄克公司
06/2026

北京福禄克世禄仪器维修和服务有限公司 电
话：400-615-1563

未经许可，本文档禁止修改

福禄克测试仪器（上海）有限公司上海维修中心 电
话：021-54402301, 021-54401908分机269

福禄克测试仪器（上海）有限公司深圳第一特约维修点
电话：0755-86337229